

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xii
	LIST OF FIGURES	xiv
 1	 INTRODUCTION	 1
	1.1 Introduction	2
	1.2 Background Study	2
	1.3 Problem Statement	4
	1.3 Objectives of Study	5
	1.4 Scope of Study	5
 2	 DIAMOND LIKE CARBON	
	2.1 Introduction	6
	2.2 Basic Concepts of Carbon	10
	2.2.1 Hybridization of Carbon	10
	2.3 Diamond-Like Carbon Structure	16
	2.4 Surface Roughness of Diamond-Like Carbon	18

2.5	Direct Current – Plasma Enhanced Chemical Vapour Deposition	19
2.5.1	Plasma	19
2.5.2	Chemical Vapour Deposition (CVD)	22
2.5.3	Plasma Enhanced Chemical Vapour Deposition (PECVD)	24
2.5.4	Direct Current – Plasma Enhanced Chemical Vapour Deposition (PECVD)	25
2.6	Subplantation Model	26
2.7	RMS Roughness	28
2.8	Analytical Techniques	29
2.8.1	Ellipsometer	29
2.8.2	Atomic Force Microscopy	31
2.8.3	Infrared Spectroscopy	34
3	METHODOLOGY	37
3.1	Introduction	37
3.2	DC-PECVD System	37
3.3	Substrate Preparation	39
3.4	Sample Preparation	41
3.5	Deposition Parameter	42
3.6	Sample Characterization	44
3.6.1	Ellipsometer	44
3.6.2	Atomic Force Microscopy (AFM)	45
3.6.3	Infrared Spectroscopy	46
4	RESULT AND DISCUSSION	48
4.1	Introduction	48
4.2	Surface Roughness Analysis	48
4.3	Thickness Analysis	56

4.4	IR Spectrum Analysis	60
5	CONCLUSION AND SUGGESTION	64
5.1	Conclusion	64
5.2	Suggestion	65
	REFERENCES	67

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Comparison of properties of diamond-like carbon films with diamond films	7
2.2	Applications of diamond and diamond-like carbon films	8
2.3	Assignments of IR vibrational frequencies of DLC films	17
3.1	Deposition parameters for DLC thin film deposition	43
4.1	RMS roughness analysis for samples in Set 1	51
4.2	RMS roughness analysis for sample in Set 2	55
4.3	Thickness analysis of DLC thin films obtained from ellipsometer measurements	57

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Ternary phase diagram for various DLC films with respect to their sp^2 , sp^3 , and hydrogen contents	9
2.2	Electron configuration at ground state of carbon and excited state.	11
2.3	The atomic orbital of sp^3 hybridization, tetrahedral geometry of sp^3 hybridization, three-dimensional representation of the methane molecule (CH_4) with sp^3 bonding and Lewis structure of methane molecule	12
2.4	The atomic orbital of sp^2 hybridization, geometry arrangement of sp^2 hybridization, three-dimensional representation of the ethane molecule (CH_4) with sp^2 bonding and Lewis structure of ethane molecule	14
2.5	The atomic orbital of sp hybridization, geometry arrangement of sp hybridization, and Lewis structure of acetylene molecule	15
2.6	IR absorption spectrum of typical DLC films obtained by CVD.	16
2.7	Growth process of a diamond film on a non-diamond substrate	20
2.8	Schematic view of plasma and discharge	22
2.9	Schematic diagram of CVD process	23

2.10	Schematic of the basic processes in subplantation, direct penetration, penetration by knock-on of a surface atom, and relaxation of a densified region.	27
2.11	A schematic diagram of an ellipsometer	30
2.12	A schematic representation of the components of an AFM.	32
2.13	Major vibrational modes for a nonlinear group, CH ₂ .	35
2.14	Simplified optical layout of a typical FTIR spectrometer.	36
3.1	A schematic diagram of direct current - plasma enhanced chemical vapour deposition (DC – PECVD) system	38
3.2	The DC-PECVD systems that has been used to deposit DLC thin films in this study	39
3.3	Ultrasonic Cleaner model Branson 3210	41
3.4	Formation of plasma during the ion beams cleaning and deposition process.	42
3.5	L117 ellipsometer that is used to determine the thickness of samples	44
3.6	The source code of BBC Ellips software used to calculate the data from ellipsometer to obtained thickness of each sample	45
3.7	SII SPI3800N probe station AFM used to characterize the surface morphology of each sample	46
3.8	Perkin Elmer Spectrum GX FT-IR and Perkin Elmer 2000R NIR FT-Raman. This tool is used to analyze the IR spectrum of each sample.	47
4.1	AFM images of DLC films deposited onto corning glass substrate with substrate temperature varied from 200°C - 550°C.	49
4.2	AFM images of DLC films deposited onto silicon substrate with substrate temperature varied from 200°C - 550°C.	50

4.3	Variation of rms roughness with substrate temperature for sample deposited onto glass and silicon substrate (Set 1).	51
4.4	AFM images of DLC films deposited onto corning glass substrate with deposition time varied from 60 minutes to 180 minutes	53
4.5	AFM images of DLC films deposited onto silicon substrate with deposition time varied from 60 minutes to 180 minutes	54
4.6	Variation of rms roughness with deposition time for sample deposited onto glass and silicon substrate (Set 2).	55
4.7	Variation of thickness with substrate temperature for glass and silicon substrates (Set 1).	58
4.8	Variation of thickness with deposition time for glass and silicon substrates (Set 2).	59
4.9	Infrared absorption peaks of samples deposited onto corning glass substrate with substrate temperature varied from 200°C – 550°C	61
4.10	Infrared absorption peak of samples deposited onto corning glass substrate with deposition time varied from 60 minutes to 180 minutes	63